



Företag/Company name		Dokumenttyp/Type of document	
Volvo Logistics Corporation		TECHNICAL SPECIFICATION	
Dokumentnamn/Name of document		Utgåva/Issue	Sida/Page
V-EMB 766		05	1 (1)
Utfärdat av (avd nr, namn, tfn, geogr plac)/Issuer (dept, name, phone, location)		Sign	Datum/Date
71300, Jörgen Jansén, 031-322 7426, ARH10			2011-02-17
Fastställt av (avd nr, namn, tfn, geogr plac)/Approved by (dept, name, phone, location)		Sign	Datum/Date
			Giltig/Valid
Mottagare (avd nr, namn, geogr plac)/Receiver (dept, name, location)			

VOLVO EMBALLAGE, V-EMB 766

Product Spacer of foamed plastic, perforated

Dimension L: 268 (±3) mm
W: 368 (±4) mm

Thickness 2,0 (±0,25) mm

Weight 0,004 kg

Material Low Density Polyethylene (LDPE)

Density 20-24 kg/m³ (Isobutan gas)

Environmental Volvo demands to be fulfilled

Colour White

Marking Material code

Unit load L4-1950 st (3 rolls á 650 pcs per roll) 174,2 m
Volume: 0,94 m³
Weight: 83,0 kg
Volvo pallet type L (emb 1), four frames (emb 21), one lid (emb 71) and one plastic cover (emb 1041). Pallet strapped with two plastic (PET) straps across the pallet

Label TY 2118 containing;
Emballage number, quantity, dispatcher and date. Attached in lower left corner on pallet short side